


### Graffiti Waster



**NEW**



#### Equipped with:

- Vertical burner with high thermal efficiency steel coil
- Auxiliary motor for burner
- Discharge valve: allows a complete discharge of the boiler
- Temperature regulator: the temperature is set-up by an electronic regulator
- Steam pressure gauge
- Temperature regulator
- Low fuel lamp
- Integrated detergent tank with detergent delivery controller by the gun
- Double pipe gasoil pump
- User-friendly control panel
- Unit can be continually refilled
- Battery and battery charger included

#### Standard equipment:

- 6.402.0080  Hose 6 m
- 6.402.0081 
- 6.402.0094 
- 6.405.0207 
- 6.402.0046 
- 6.402.0099 
- 3.749.0475 
- 4.408.0009 
- 2 x 4.407.0079 Steam nozzle

#### Optional:

- 6.402.0080 Steam gun with hose (3,5 m)
- 6.402.0085 Steam gun with hose (10 m)
- 6.402.0093 Steam gun with hose (15 m)
- 6.402.0090 Steam gun with hose (20 m)
- 0.011.0001 Calibrated sand (6 x 5 kg)

	Graffiti Waster
Code	8.628.0013
Max steam pressure/temperature	10 bar / 178° C
Absorbed power	350 W / 1 x 12 DC 75 Ah C5
Steam production	37.5 kg/h
Burner type/fuel consumption	Diesel / 3 l/h
Water tank/fuel tank capacity	25 l / 25 l